


UNIT : mm

POS. NO.	DENOTES CONTACT CLOSURE TO COMMON ⁽²⁾								
	①	③							
1	0	0							
2	1	0							
3	1	1							
4	0	1							
5	0	0							
6	1	0							
7	1	1							
8	0	1							
9	0	0							
10	1	0							
11	1	1							
12	0	1							
13	0	0							
14	1	0							
15	1	1							
16	0	1							



- NOTES:
1. ENCODER CODE : 2 BIT BINARY
 2. COMINATION : 16 COMBINATION
 3. CONTACT RESISTANCE : 500 OHMS MAX.
 4. ROTATIONAL ANGLE : 360°
 5. DETENT : 16 DETENT
 6. BUSHING MATERIAL : BRASS
SHAFT MATERIAL : ALUM
 7. MOMENTARY SWITCH : NONE.
 8. HARDWARE : Nut : 45T-3 ; Washer : 1220A
 9. FOR ADDITIONAL REQUIREMENTS SEE CTS ENG. SPEC. # EN-SPE-288101B

TRUTH TABLE (CW ROTATION)

1 → ON
0 → OFF

COMPONENTS TAIWAN LTD. KAOHSIUNG, TAIWAN		CUSTOMER :	Leobodnar
CTS PART NO.	288S0971	REV	
CUSTOMER PART NO.		SAMPLE REQUEST:	288-10172
ISSUED DATE :	03/05/21 ¹	CHECKED BY :	S.S.Chen
CTS TYPE :	CR-T288RE	APPROVED BY :	HKHu
TOLERANCE UNLESS OTHERWISE SPECIFIED .X (1 PLACE) : ± 0.3 .XX (2 PLACE) : ± 0.13 ANGLE : ± 5°		CUSTOMER APPROVAL: (SIGNATURE & DATE) 9/3/21	